



Features

- Complies with IEEE 802.3/802.3u/802.3ab standards.
- Integrates 10/100/1000Mbps transceiver.
- Supports PCI-E slot.
- Crossover Detection & Auto-correction.
- Supports wake-on-LAN and remote wake-up.
- Supports Full Duplex flow control (IEEE8.2.3x).
- Supports transmission/receiving FIFO (8K/64K).
- Supports Windows XP/Vista/7, Linux.



Model / Product Description	PX1000 / 10/100/1000Mbps PCI-E Adapter
Port	10/100/1000Mbps RJ45 port x1
Standards	IEEE 802.3/802.3u, 802.3ab
Transmission Rate	10/100Mbps for Full/Half-Duplex modes
LED Indicator	10M (Link/Activity/Speed) LED x1 100M (Link/Activity/Speed) LED x1 1000M (Link/Activity/Speed) LED x1 FDX (Full Duplex) LED x1
System Requirement	Windows 10 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP (32/64bits) Mac OS X 10.4~10.7
Environment	Operating Temperature: 0°C~40 °C (32 °F~104°F) Storage Temperature: -40°C~70 °C (-40 °F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Package Contents	1 x PX1000 Network Adapter 1 x Resource CD 1 x Low Profile Bracket